

A tantalum container was loaded with a graphite insert and closed \

Heating Started Finished

Date: 190417

Temp	TGHT		TBHT		Vacuum
	Voltage	Current	Voltage	Current	
1062	3.0	230.63	1.61	132.56	8.94E-07
1070	3.0	233.34	1.61	133.06	8.89E-07
1311	4.3	301.50	2.15	169.41	8.51E-07
1320	4.3	303.56	2.17	170.34	8.60E-07
1358	4.5	312.00	2.23	174.56	8.77E-07
1384	4.6	318.56	2.29	178.31	9.13E-07
1403	4.6	321.09	2.31	179.84	9.20E-07
1424	4.8	327.65	2.37	183.09	9.46E-07
1470	4.9	336.38	2.45	188.31	9.66E-07
1495	5.1	342.47	2.50	191.50	1.01E-07
1520	5.2	350.16	2.68	202.91	9.29E-07
1538	5.3	356.91	2.75	207.44	9.40E-07
1568	5.5	363.65	2.82	211.56	9.88E-07
1615	5.8	377.53	2.94	218.75	1.11E-07
1645	5.9	386.72	3.02	224.34	1.18E-07
1650	6.0	389.72	3.05	225.25	1.19E-07
1674	6.1	394.50	3.09	227.88	1.25E-07
1715	6.3	403.41	3.18	233.03	9.00E-07
1722	6.3	404.44	3.18	233.09	1.00E-06
1781	6.7	425.25	3.18	233.13	1.19E-06
1832	7.0	444.65	3.18	233.09	1.38E-06
1852	7.2	448.50	3.19	233.09	1.42E-06
1860	7.2	454.13	3.19	233.13	1.46E-06
1875	7.4	459.09	3.19	233.13	1.55E-06
1970	8.0	489.75	3.20	233.13	1.39E-06
1990	8.1	494.53	3.20	233.13	1.41E-06
1994	8.1	495.47	3.20	233.09	1.46E-07
1996	8.1	495.56	3.20	233.09	1.45E-06
1995	8.3	504.00	3.02	233.19	3.08E-07
1986	8.3	503.25	3.20	3233.03	1.29E-07
2001	8.3	503.16	3.20	233.03	1.25E-07
1992	8.4	504.25	3.20	233.03	1.27E-07
1987	8.3	503.25	3.20	233.09	1.48E-07
1989	8.4	503.44	3.20	233.06	1.07E-07