ISAC Storage Vault Status as of May 16 2012

T					ge vaan Status as of may			
Tray #	Pail #	Target	Installed (m/d/y)	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
1A								
1B	94	SiC #26	05/05/16	118mSv/hr				
1C	93	UC _x #3	03/13/12	11.7mSv/hr				
			05/31/11	120mSv/hr				
2A	87	SiC #25	12/15/11	10.7mSv/hr	Not Assayed			
			10/20/10	143mSv/hr				
2B	83	SiC #23	12/15/10	6.72mSv/hr	Not Assayed			
			10/20/10	93mSv/hr				
2C	82	Ta #34	12/14/11	4.33mSv/hr	Assayed			
					-			
3A								
			09/29/11	111mSv/hr				
3B	90	Ta #36						
			01/14/11	1.7mSv/hr	Put back in on Jan 5/12			
3C	86	UC _x #1	12/12/11	0.19mSv/hr	Assayed	01/04/12		
			12/08/10	27mSv/hr				
4A	84	SiC #24	11/08/11	1.99mSv/hr	Assayed			
			02/09/10	160mSv/hr				
4B	76	Nb #4	11/10/11	3.89mSv/hr	Assayed			
4C								
			10/05/11	8.91mSv/hr	Put back in on Jan 5/12			
5A	91	UC _x #2	12/12/11	1.12mSv/hr	Assayed	01/04/12		
		X	01/11/11	230 mSv/hr		JJ		
5B	85	Nb #5	3 .,,					
5C								
30	<u> </u>							

All readings are taken at 1m from centre of pail. Sealant (111) is used under lid rim. No contamination found unless other wise noted.

All lids have the lever lock ring and cable lifting setup. This ring must be locked with a thin piece of metal before shipping.

Tray#	Pail #	Target	Date Installed	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
6A								
			07/14/09	81.0mSv/hr				
6B	68	Ta #27	12/14/11	2.76mSv/hr	Assayed			
			07/25/11	411mSv/hr				
6C	88	Ta#35						
			06/10/10	116mSv/hr				
7A	75	Ta#31	12/15/11	4.17mSv/hr	Assayed			
			11/16/11	239mSv/hr				
7B	92	TaC#1						
			08/25/10	292mSv/hr				
7C	81	ZrC#5	12/15/11	13.7mSv/hr	Not Assayed			
8A								
			07/16/10	124mSv/hr				
8B	78	Ta#32						
			07/16/10	70.1mSv/hr				
8C	79	SiC#22	12/14/11	1.93mSv/hr	Assayed			
Tray #		ion of Item	Date Installed	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
	Used source tray			5.6 to 16.4				
	from TM #2			mSv/hr thru				
				360∘				
9			01/15/09					
	Used source tray			1.66 to 3.50	The source tray was			
	from TM #1			mSv/hr thru	taken apart for inspection			
				360°				
10			05/12/11					

All readings are taken at 1m from centre of pail. Sealant (111) is used under lid rim. No contamination found unless other wise noted.

All lids have the lever lock ring. This ring must be locked with a thin piece of metal before shipping.