ISAC Storage Vault Status as of Decembe	er 6 2012
---	-----------

				ISAC SIDIAYE	vault Status as of Decem			
Tray #	Pail #	Target	Installed (m/d/y)	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
			09/07/12	42.0mSv/hr				
1A	98	UO#3				1		
1B	94	SiC #26	05/05/12	118mSv/hr		-		
			03/13/12	11.7mSv/hr				
1C	93	UC _x #3	10/31/12	1.89mSv/hr	Assayed			
2A	102	UC #5	12/06/12	32.6mSv/hr				
			10/20/10	143mSv/hr				
2B	83	SiC #23	10/31/12	5.30mSv/hr	Assayed			
2C								
3A	96	SiC #27	07/06/12	178mSv/hr				
			09/29/11	111mSv/hr				
3B	90	Ta #36						
3C	99	UC _x #4	09/14/12	55.3mSv/hr				
						_		
4A	101	NiO #1	10/24/12	35.5mSv/hr				
4B								
						-		
4C								
						-		
5A								
			01/11/11	230 mSv/hr		-		
5B	85	Nb #5	11/01/12	7.70mSv/hr	Assayed			
			06/11/12	152mSv/hr		-		
5C	95	Nb #6						
All readings are taken at 1m from centre of pail. Sealant (111) is used under lid rim. No contamination found unless other wise noted.								
All lids have the lever lock ring and cable lifting setup. This ring must be locked with a thin piece of metal before shipping.								

Tray #	Pail #	Target	Installed (m/d/y)	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
			11/09/12	178mSv/hr				
6A	103	Nb # 7						
			08/02/12	226 mSv/hr	Bolts might be contaminated			
6B	97	Ta#38						
			07/25/11	411mSv/hr				
6C	88	Ta#35						
7A								
			11/16/11	239mSv/hr				
7B	92	TaC#1						
		7.045	08/25/10	292mSv/hr	• •			
7C	81	ZrC#5	11/01/12	5.80mSv/hr	Assayed			
8A								
0A								
8B								
00								
8C								
Tray #	Descripti	ion of Item	Date Installed	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
nay "	Used source tray			5.6 to 16.4	Tray surveyed on	Date Removed	(incounty)	
	from TM #2			mSv/hr thru	11/02/12			
				360°	2.07 to 4.39 mSv/hr			
					though 360°			
9			01/15/09			1		
	Used so	ource tray		1.66 to 3.50	The source tray was			
		TM #1		mSv/hr thru	taken apart for inspection			
				360°	Tray surveyed on	1		
					11/02/12			
					1.83 to 3.23 mSv/hr			
10			05/12/11		though 360°			
All					t (111) is used under lid rim.			
All lids have the lever lock ring. This ring must be locked with a thin piece of metal before shipping.								