## ISAC Storage Vault Status as of July 31 2013

Tray #	Pail #	Target	Installed (m/d/y)	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments			
		<u> </u>									
1A											
1B	94	SiC #26	05/05/12	118mSv/hr							
1C											
						_					
2A											
						-					
2B											
	105	0:0, 1/00	05/31/13	24.8mSv/hr		-					
2C	105	SiC #28									
3A	96	SiC #27	07/06/12	178mSv/hr		-					
ЗА	90	510 #27	07/06/12	111mSv/hr							
3B	90	Ta #36	09/29/11	4.64mSv/hr	Assayed	-					
30	90	Ta #30	00/20/13	4.041137/11	Assayeu						
3C						-					
			10/24/12	35.5mSv/hr							
4A	101	NiO #1	06/20/13	1.50mSv/hr	Assayed	-					
			00/20/10								
4B	104	TiC #3	01/15/13	98.7mSv/hr		-					
4C	106	Ta #39	07/02/13	95.3mSv/hr		1					
5A	107	Ta #40	07/29/13	224mSv/hr		]					
			01/11/11	230mSv/hr							
5B	85	Nb #5	06/20/13	3.05mSv/hr	Assayed						
			06/11/12	152mSv/hr							
5C	95	Nb #6									
All readings are taken at 1m from centre of pail. Sealant (111) is used under lid rim. No contamination found unless other wise noted.											
All lids have the lever lock ring and cable lifting setup. This ring must be locked with a thin piece of metal before shipping.											

Tray #	Pail #	Target	Installed (m/d/y)	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
			11/09/12	178mSv/hr				
6A	103	Nb # 7						
			08/02/12	226 mSv/hr	Bolts might be contaminated			
6B	97	Ta#38						
			07/25/11	411mSv/hr				
6C	88	Ta#35	06/20/13	8.26mSv/hr	Assayed			
7A								
			11/16/11	239mSv/hr				
7B	92	TaC#1	06/20/13	3.55mSv/hr	Assayed			
			08/25/10	292mSv/hr				
7C	81	ZrC#5	06/20/13	2.65mSv/hr	Assayed			
0.4							-	
8A								
8B							-	
00								
8C								
Tray #	Description of Item		Date Installed	Reading (mSv/Hr)	Comments	Date Removed	Reading(mSv/Hr)	Comments
		ource tray		5.6 to 16.4	Tray surveyed on		(income)	
		TM #2		mSv/hr thru	11/02/12			
				360°	2.07 to 4.39 mSv/hr			
					though 360°			
9			01/15/09					
	Used source tray from TM #1			1.66 to 3.50	The source tray was			
				mSv/hr thru	taken apart for inspection			
				360°	Tray surveyed on			
					11/02/12			
					1.83 to 3.23 mSv/hr			
10			05/12/11		though 360°			
All					t (111) is used under lid rim.			
	All lid	<mark>s have th</mark> e	e lever lock r	<mark>ring. This r</mark> in	<mark>g must be locked with a</mark>	a thin piece	of metal befo	ore shipping.